



ENGINEERING-FIRST AUTOMATION

# HIGH-SPEED KNOCKOFF

Encoder-synchronized reject with product width targeting—triggered by a fail digital output to a matched reject conveyor.

SSI's High-Speed Knockoff is a fast, repeatable reject mechanism built for high throughput lines with tight reject windows. An SSI supplied **encoder mounts to the conveyor drive shaft** and tracks product position by pulse count (distance based). A **fail digital output** from upstream equipment triggers the reject event, and the HMI lets operators set **product width** and **offset** so only the appropriate knockoff fingers activate—directing the specific part onto a speed matched reject conveyor.

## SYSTEM OVERVIEW



- Triggered by a fail digital output (discrete I/O)
- Enter product width + offset on the HMI for targeting
- Selective finger window reduces disturbance
- Speed-matched reject conveyor handoff

## ENCODER-SYNCHRONIZED TRACKING

- Distance based tracking using pulse counts
- Maintains reject alignment through speed changes
- Eliminates time delay guessing

## PRODUCT-WIDTH TARGETING

- Operator enters product width on the HMI
- System fires only the fingers within that width window
- “Crescendo” activation for controlled contact

## DIGITAL TRIGGER INTERFACE

- Fail digital output triggers reject event
- Debounce/one shot behavior as required
- Counts every reject for reporting on HMI

## REJECT CONVEYOR HANDOFF

- Dedicated reject conveyor (speed-matched)
- Reject direction and layout customizable
- Stable handoff reduces jams and rework

## WHY ENCODER-BASED REJECT MATTERS

Encoder-synchronized tracking keeps the reject window tied to actual conveyor movement. Back-to-back products and variable spacing are supported, but a minimal gap is required based on product and speed.



# HIGH-SPEED KNOCKOFF | DETAILS

Drive-shaft encoder tracking • Width-based finger window • Digital fail trigger

## HOW IT WORKS

- 1 Configure** — On the HMI, enter product width and adjust the offset for your reject point.
- 2 Track** — The SSI supplied encoder on the conveyor drive shaft tracks product position by pulse count.
- 3 Trigger** — Upstream equipment asserts a fail digital output; the system assigns that product a tracked reject position.
- 4 Reject** — Only the fingers in the width window activate and knock the product onto the matched reject conveyor; reject counts increment.



## INCLUDED

- SSI supplied conveyor encoder + tracking setup
- Digital fail input integration (discrete I/O)
- HMI setup: width, offset, tuning, and reject counts
- Commissioning support and diagnostics foundation

## OPTIONAL

- Stack light and supervisor notification integration
- Custom reject conveyor and discharge configurations
- Additional I/O handshakes (ready/fault) as scoped

## PROJECT INPUTS (FOR SCOPING)

- Conveyor drive shaft details for encoder mounting (speed range, shaft access)
  - Product width/length, weight, and stability
  - Line speed and **minimum gap** between products
  - Reject conveyor layout and discharge direction
  - Trigger source (fail digital output) and required interlocks
- SSI defines timing, finger window behavior, and safety scope based on real line constraints and acceptance criteria.

**Next step: Share line layout + speed/spacing targets • Request a Quote**